558™



Perfect for anyone that doesn't like to sacrifice. The 558 is compatible with all Gen I-III night vision devices and features an adjustable, locking, quick-detach mount that offers instant removal.

ORDER CODE


558.A65

BLACK

TECHNICAL SPECIFICATIONS

L × W × H	5.6" × 2.2" × 2.9" (142.2 × 55.9 × 73.7mm)
WEIGHT	13.8 oz (391.2g)
WATER-RESISTANT	33 ft (10m) depth
MOUNT	1" Weaver or MIL-STD 1913 rail
WINDAGE AND ELEVATION	0.5 MOA per click
BRIGHTNESS	20 daylight settings 10 additional settings for Gen I through III+ night vision devices
POWER SOURCE	2 × 1.5 V AA batteries — Supports lithium, alkaline, or rechargeable
BATTERY LIFE	Lithium: 2,500 continuous hours at nominal setting 12 at room temperature Alkaline: 2,200 continuous hours at nominal setting 12 at room temperature
OPERATING TEMPERATURE	-40°F to 140°F (-40°C to 60°C)
COUNTRY OF ORIGIN	Made in USA

RETICLE



0

EOTECHINC.COM

EXPORT RESTRICTIONS: Export of this product is strictly controlled and enforced by the U.S. Department of Commerce, Bureau of Industry and Security, as prescribed in the Export Administration Regulation (EAR), Title 15, Code of Federal Regulations, Parts 730-774. EOTECH LLC does not authorize any of its dealers or distributors to export this commodity without prior, written authorization, and will not provide warranty or post-sales support of unauthorized international exports.

© 2022 EOTECH, LLC.

All rights reserved. EOTECH®, HWS® and Vudu® are registered trademarks of EOTECH, LLC.

CONTACT

46900 Port St.
Plymouth, MI 48170 USA

+1-888-368-4656