vudu
1-8X24 SFP™



Like other Vudu scopes, the 1–8X24 SFP features aircraft-grade aluminum construction and bright XC High-Density glass, surgically precise turrets, and intuitive push-button reticle illumination controls. The HC3 quad-level BDC reticle features a precise 0.5-MOA illuminated center dot and 2-, 5-, 8.5- and 12.5-MOA subtensions on the vertical axis (at 8X power). The scope's field of view at 100 yards is 105.8 feet at 1X and 13.2 feet at 8X.

ORDER CODE


VDU1-8SFHC3

BLACK

TECHNICAL SPECIFICATIONS

MAGNIFICATION	1-8X
FOCAL PLANE	Second
TUBE DIAMETER	30mm
OBJECTIVE DIAMETER	24mm
ILLUMINATED	Yes
BATTERY TYPE	CR2032
OVERALL LENGTH	10.9" (278mm)
WEIGHT	20.8 oz (589.7g)
EYE RELIEF	1X: 3.46–4.09" (88–104mm) / 8X: 3.54–3.9" (90–99mm)
FIELD-OF-VIEW @ 100 YDS	1X: 105.8 ft (32.2 m) / 8X: 13.2 ft (4 m)

RETICLE



HC3

RETICLE SPECIFICATIONS	HC3
ADJUSTMENT GRADUATION PER CLICK	0.25 MOA
ADJUSTMENT GRADUATION PER ROTATION	20 MOA
TOTAL ELEVATION TRAVEL	100 MOA
TOTAL WINDAGE TRAVEL	80 MOA

EOTECHINC.COM

EXPORT RESTRICTIONS: Export of this product is strictly controlled and enforced by the U.S. Department of Commerce, Bureau of Industry and Security, as prescribed in the Export Administration Regulation (EAR), Title 15, Code of Federal Regulations, Parts 730-774. EOTech LLC does not authorize any of its dealers or distributors to export this commodity without prior, written authorization, and will not provide warranty or post-sales support of unauthorized international exports.

© 2022 EOTECH, LLC.

All rights reserved. EOTECH®, HWS® and Vudu® are registered trademarks of EOTECH, LLC.

CONTACT

46900 Port St.
Plymouth, MI 48170 USA

+1-888-368-4656