vudu
3.5-18X50 FFP™



The Vudu 3.5-18X50 provides a robust 34mm tube, XC High-Density glass, and is loaded with other performance features required to take that precise long-range shot. The oversized and precision-machined turrets, with EZ Chek Zero Stop feature, let you quickly dial adjustments and return to zero, even in low-light conditions. The side-mounted parallax adjustment allows you to easily dial-in the reticle focus.

ORDER CODES


VDU3-18FFH59
VDU3-18FFMD1
VDU3-18FFMD2

BLACK

TECHNICAL SPECIFICATIONS

MAGNIFICATION	3.5-18X
FOCAL PLANE	First
TUBE DIAMETER	34mm
OBJECTIVE DIAMETER	50mm
ILLUMINATED	Yes
BATTERY TYPE	CR2032
OVERALL LENGTH	15.13" (384mm)
WEIGHT	33.6 oz (952g)
EYE RELIEF	3.5X: 3.58–3.97" (91-101mm) / 18X: 3.54–3.97" (90-101mm)
FIELD-OF-VIEW @ 100 YDS	3.5X: 29.5 ft (9 m) / 18X: 5.7 ft (1.74 m)


RETICLES



MD1



MD2



HORUS® H59™

RETICLE SPECIFICATIONS	MD1	MD2	H59
ADJUSTMENT GRADUATION PER CLICK	0.1 MRAD	0.25 MOA	0.1 MRAD
ADJUSTMENT GRADUATION PER ROTATION	10 MRAD	25 MOA	10 MRAD
TOTAL ELEVATION TRAVEL	29 MRAD	100 MOA	29 MRAD
TOTAL WINDAGE TRAVEL:	23 MRAD	80 MOA	23 MRAD

EOTECHINC.COM

EXPORT RESTRICTIONS: Export of this product is strictly controlled and enforced by the U.S. Department of Commerce, Bureau of Industry and Security, as prescribed in the Export Administration Regulation (EAR), Title 15, Code of Federal Regulations, Parts 730-774. EOTech LLC does not authorize any of its dealers or distributors to export this commodity without prior, written authorization, and will not provide warranty or post-sales support of unauthorized international exports.

© 2022 EOTECH, LLC.
All rights reserved. EOTECH®, HWS® and Vudu® are registered trademarks of EOTECH, LLC.

CONTACT
46900 Port St.
Plymouth, MI 48170 USA
+1-888-368-4656